

SKS-HT848 5.1-CHANNEL HOME THEATER SPEAKER SYSTEM



Onkyo Takes the Guesswork out of Speaker Selection

Whether you're into film, music, or gaming, Onkyo has you covered with its versatile SKS-HT848 5.1-channel surround sound speaker system. Newcomers to home theater and experienced users alike will delight in the sensitivity and balance of this professionally calibrated package. A pair of bass-reflex floor-standing speakers—now available in 'natural' finish—feature two high-quality 8 cm woofers and a balanced-dome tweeter in each cabinet, while the center speaker runs a high-performance acoustic-suspension cabinet and two 8 cm woofers. A set of compact satellite surround speakers augments a detailed and immersive mid-range. Boosting bottom-end sound is the SKW-770 down-firing subwoofer, which has a large 25 cm cone for 120 W of continuous power. Married to a suitable Onkyo receiver, the SKS-HT848 speaker system is sure to add to the magic of movie night.

SKF-890

2-Way Bass Reflex Front Speakers

- 8 cm Cone Woofer x 2
- 2.5 cm Balanced-Dome Tweeter
- Max. Input Power: 130 W
- Gloss Finished Top and Front Panels
- Color-Coded Speaker Terminals and Cable
- Impedance: 6 Ω

SKC-548C

Full-Range Acoustic-Suspension Center Speaker

- 8 cm Cone Woofer x 2
- Max. Input Power: 120 W
- Color-Coded Speaker Terminals and Cable
- Impedance: 6 Ω
- Magnetically Shielded

SKR-548

Full-Range Bass Reflex Surround Speakers

- 8 cm Cone
- Max. Input Power: 120 W
- Color-Coded Speaker Terminals and Cable
- Impedance: 6 Ω

SKW-770

Bass Reflex Powered Subwoofer

- 25 cm Cone
- Rated Output Power: 120 W (Minimum Continuous Power, 4 Ω , 100 Hz, 1%, IEC)
- Down-Firing
- Gloss Finished
- Output Level Control

SPECIFICATIONS

Speaker Type	2-way, bass reflex	Rated Output Power	Subwoofer 120 W (Minimum continuous power, 4 Ω , 100 Hz, 1%, IEC)
Front	Full-range, acoustic-suspension	Nominal Impedance	Front/Center/Surround 6 Ω
Center	Full-range, bass reflex	Input Sensitivity/Impedance	Subwoofer 550 mV/20 k Ω
Surround	Bass reflex, powered	General	
Subwoofer		Dimensions (W x H x D)	Front 262 x 1050 x 262 mm
Drivers		Center 230 x 103 x 115 mm	Surround 101 x 161 x 115 mm
Front	8 cm cone woofer x 2	Subwoofer 275 x 507 x 411 mm	Weight
Center	2.5 cm balanced-dome tweeter	Front 5.2 kg	Center 1.3 kg
Surround	8 cm cone	Surround 0.7 kg	Subwoofer 11.6 kg
Subwoofer	25 cm cone	CARTON	
Frequency Response		Dimensions (W x H x D)	1139 x 561 x 515 mm
Front	55 Hz-50 kHz	Weight	31.5 kg
Center	80 Hz-20 kHz		
Surround	80 Hz-20 kHz		
Subwoofer	25 Hz-150 Hz		
Output Sound Pressure Level			
Front	79.5 dB/W/m		
Center	84 dB/W/m		
Surround	80 dB/W/m		
Max. Input Power			
Front	130 W		
Center/Surround	120 W		

Due to a policy of continuous product improvement, Onkyo reserves the right to change specifications and appearance without notice.