

SKS-HT230

5.1-CHANNEL HOME THEATRE SPEAKER SYSTEM

ONKYO
IMAGINATIVE SIGHT & SOUND

THE HOME THEATRE SPEAKER SYSTEM TO MATCH THE TVs OF TODAY—AND TOMORROW



SKF-230F

2-Way Bass Reflex Front Speakers

- 8 cm cone woofer
- 2.5 cm balanced-dome tweeter
- Slit-duct Air Drive Technology for powerful and natural sound
- Magnetically Shielded
- Rigid aluminum cabinet

SKC-230C

2-Way Bass Reflex Centre Speaker

- 8 cm cone woofer
- 2.5 cm balanced-dome tweeter
- Slit-duct Air Drive Technology for powerful and natural sound
- Magnetically Shielded
- Rigid aluminum cabinet

SKM-230S

2-Way Bass Reflex Surround Speakers

- 8 cm cone woofer
- 2.5 cm balanced-dome tweeter
- Slit-duct Air Drive Technology for powerful and natural sound
- Magnetically Shielded
- Rigid aluminum cabinet

SKW-150X

Powered Subwoofer

- Built-in 150 W dynamic power amplifier for powerful and natural sounding bass
- 20 cm cone woofer
- Auto standby/on indicator
- Output level knob

SPECIFICATIONS

Speaker Type	
Front	2-Way, Bass Reflex
Centre	2-Way, Bass Reflex
Surround	2-Way, Bass Reflex
Subwoofer	Bass Reflex Powered
Drivers	
Front	8 cm Cone (woofer) / 2.5 cm Balanced-Dome
Centre	8 cm Cone (woofer) / 2.5 cm Balanced-Dome
Surround	8 cm Cone (woofer) / 2.5 cm Balanced-Dome
Subwoofer	20 cm Cone
Frequency Response	
Front	65 Hz-35 kHz
Centre	65 Hz-35 kHz
Surround	65 Hz-35 kHz
Subwoofer	30 Hz-150 Hz
Crossover Frequency	
Front/Centre/Surround	6.5 kHz / 6.5 kHz / 6.5 kHz
Sensitivity	
Front	80 dB/W/m
Centre	80 dB/W/m
Surround	80 dB/W/m
Subwoofer	220 mV (Line input)
Max. Input Power	
Front/Centre/Surround/Subwoofer ..	100 W / 100 W / 100 W / 150 W (Dynamic)
Nominal Impedance	
Front/Centre/Surround	8 Ω / 8 Ω / 8 Ω
Input Impedance	
Subwoofer	15 kΩ
GENERAL	
Dimensions (W x H x D)	
Front	130 x 340 x 91 mm
Centre	340 x 130 x 91 mm
Surround	130 x 340 x 91 mm
Subwoofer	235 x 518 x 411 mm
Weight	
Front/Centre/Surround/Subwoofer ..	1.6 kg / 1.6 kg / 1.6 kg / 12.6 kg

*All include color-coded speaker terminals and speaker cable (SKF-230F, SKC-230C, SKM-230S)
Exclusive speaker bases supplied (SKF-230F, SKC-230C)

Due to a policy of continuous product improvement, Onkyo reserves the right to change specifications and appearance without notice.

ONKYO
IMAGINATIVE SIGHT & SOUND

Onkyo Corporation Business Unit Dept.: 2-1, Nisshin-cho, Neyagawa-shi, OSAKA 572-8540, JAPAN Tel: 072-831-8005 Fax: 072-833-5222
<http://www.onkyo.com>

Onkyo China Limited Units 2102-2107, Metroplaza Tower I, 223 Hing Fong Road, Kwai Chung, N. T., HONG KONG, SAR of China Tel: 852-2429-3118 Fax: 852-2428-9039
<http://www.onkyochina.com>