

SKS-HT728

5.1-Channel Home Theatre Speaker System

BLACK



Beautifully Balanced Surround-Sound System with Tallboy Front Speakers

For maximum audio impact, your multichannel Onkyo receiver should be accompanied by a full-blooded surround-sound speaker set. Fitting the bill is the new SKS-HT728, a 5.1-channel system that injects power and vitality into all your movies, games, and music. The highlight, both visually and aurally, is a pair of dual-drive, floor-standing tallboy front speakers rated conservatively at 130 W. In concert with the two-way center and full-range surround speakers—each also rated 130 W—they deliver stunningly detailed high- and mid-range frequencies. Meanwhile, at the bottom end, a superbly calibrated 290 W subwoofer adds visceral heft to bass notes and low frequency effects.

SKF-770 Dual-Drive 2-Way Front Speakers

- 8 cm Cone Woofer x 2
- 2.5 cm Balanced-Dome Tweeter
- Max. Input Power: 130 W
- Gloss-Finished Top Panel

SKC-770 Dual-Drive 2-Way Center Speaker

- 8 cm Cone Woofer x 2
- 2.5 cm Balanced-Dome Tweeter
- Max. Input Power: 130 W
- Gloss-Finished Side Panels

SKR-770 Full-Range Surround Speakers

- 8 cm Cone
- Max. Input Power: 130 W

Note: All speakers feature an impedance of 6 Ω and color-coded speaker terminals and cable. And all except the front speakers are wall-mountable.

SKW-770 Bass Reflex Powered Subwoofer

- 25 cm Cone
- Max. Output Power: 290 W
- Output-Level Control
- Gloss-Finished Front Panel

SPECIFICATIONS

Speaker Type	
Front	Dual-drive, 2-way
Center	Dual-drive, 2-way
Surround	Full-range
Subwoofer	Bass reflex, powered
Drivers	
Front	8 cm cone woofer x 2 2.5 cm balanced-dome tweeter
Center	8 cm cone woofer x 2 2.5 cm balanced-dome tweeter
Surround	8 cm cone
Subwoofer	25 cm cone
Frequency Response	
Front	55 Hz–50 kHz
Center	60 Hz–50 kHz
Surround	80 Hz–20 kHz
Subwoofer	25 Hz–150 Hz
Output Sound Pressure Level	
Front	79.5 dB/W/m
Center	79 dB/W/m
Surround	81 dB/W/m
Max. Input Power	
Front/Center/Surround	130 W
Max. Output Power	
Subwoofer	290 W

Nominal Impedance

Front/Center/Surround 6 Ω

Input Sensitivity/Impedance

Subwoofer 140 mV/20 kΩ

GENERAL

Dimensions (W x H x D)

Front (not including speaker base)
262 x 1050 x 262 mm
Center
430 x 115 x 121 mm
Surround
115 x 230 x 96 mm
Subwoofer
275 x 507 x 411 mm

Weight

Front 5.2 kg
Center 2.2 kg
Surround 1.0 kg
Subwoofer 11.6 kg

■ CARTON

Dimensions (W x H x D) 683 x 1150 x 558 mm

Weight 35 kg

Due to a policy of continuous product improvement, Onkyo reserves the right to change specifications and appearance without notice.