

SKS-HT890 5.1-CHANNEL HOME THEATER SPEAKER SYSTEM



Onkyo Takes the Guesswork out of Speaker Selection

Whether you're into film, music, or gaming, Onkyo has you covered with its versatile SKS-HT890 5.1-channel surround sound speaker system. Newcomers to home theater and experienced users alike will delight in the sensitivity and balance of this professionally calibrated package. A pair of bass-reflex floor-standing speakers—now available in 'natural' finish—feature two high-quality 8 cm woofers and a balanced-dome tweeter in each cabinet, while the center speaker runs a high-performance acoustic-suspension cabinet and an 8 cm woofer. A set of compact satellite surround speakers augments a detailed and immersive mid-range. Boosting bottom-end sound is the SKW-501E down-firing subwoofer, which has a large 20 cm cone for 80 W of continuous power. Married to a suitable Onkyo receiver, the SKS-HT890 speaker system is sure to add to the magic of movie night.

SKF-890

2-Way Bass Reflex Front Speakers

- 8 cm Cone Woofer x 2
- 2.5 cm Balanced-Dome Tweeter
- Max. Input Power: 130 W
- Gloss Finished Top and Front Panels
- Color-Coded Speaker Terminals and Cable
- Impedance: 6 Ω

SKC-548

Full-Range Acoustic-Suspension Center Speaker

- 8 cm Cone Woofer
- Max. Input Power: 120 W
- Color-Coded Speaker Terminals and Cable
- Impedance: 6 Ω
- Magnetically Shielded

SKR-548

Full-Range Bass Reflex Surround Speakers

- 8 cm Cone
- Max. Input Power: 120 W
- Color-Coded Speaker Terminals and Cable
- Impedance: 6 Ω

SKW-501E

Bass Reflex Powered Subwoofer

- 20 cm Cone
- Rated Output Power: 80 W (Minimum Continuous Power, 4 Ω, 100 Hz, 1%, IEC)
- Down-Firing
- Gloss Finished
- Output Level Control

SPECIFICATIONS

Speaker Type		Rated Output Power	
Front	2-way, bass reflex	Subwoofer	80 W (Minimum continuous power, 4 Ω, 100 Hz, 1%, IEC)
Center	Full-range, acoustic-suspension	Nominal Impedance	Front/Center/Surround 6 Ω
Surround	Full-range, bass reflex	Input Sensitivity/Impedance	Subwoofer 410 mV/20 kΩ
Subwoofer	Bass reflex, powered	General	
Drivers		Dimensions (W x H x D)	
Front	8 cm cone woofer x 2 2.5 cm balanced-dome tweeter	Front	262 x 1050 x 262 mm
Center	8 cm cone	Center	230 x 103 x 115 mm
Surround	8 cm cone	Surround	101 x 161 x 115 mm
Subwoofer	20 cm cone	Subwoofer	230 x 425 x 412 mm
Frequency Response		Weight	
Front	55 Hz-50 kHz	Front	5.2 kg
Center	80 Hz-20 kHz	Center	0.9 kg
Surround	80 Hz-20 kHz	Surround	0.7 kg
Subwoofer	27 Hz-150 Hz	Subwoofer	9.1 kg
Output Sound Pressure Level		CARTON	
Front	79.5 dB/W/m	Dimensions (W x H x D)	1139 x 561 x 515 mm
Center	82 dB/W/m	Weight	29 kg
Surround	80 dB/W/m		
Max. Input Power			
Front	130 W		
Center/Surround	120 W		

Due to a policy of continuous product improvement, Onkyo reserves the right to change specifications and appearance without notice.