

SKS-HT993THX 7.1-Channel Home Theater Speaker System



BLACK

THX A-OMF
1778 PLUS

Time to Get Serious About THX® Reference Sound

If you're serious about experiencing THX-certified theater reference surround-sound in your entertainment space, look no further than the SKS-HT993THX package from Onkyo. Born of a legendary 70-year Hi-Fi heritage, each speaker has been painstakingly designed, tuned, and independently tested by Onkyo and THX technicians to ensure film soundtracks explode with rich layers of detail and immersive wide-spectrum dynamics. Solid MDF cabinets are fitted with either one (surrounds) or two (front LR and center) A-OMF woofer diaphragms that use layers of lightweight polyethylene naphthalate, cotton weave, and aramid to achieve exceptional speed and accuracy, while high-quality 2.5 cm soft-dome tweeters cleanly extend treble out to 45 kHz. And because the speakers are sealed, you can position them almost anywhere—it's even possible to wall-mount the surrounds—without compromising bass power or clarity. Rounding out this 7.1-channel speaker package is a 125 W powered subwoofer, it's high-capacity cabinet and 30 cm front-firing cone filling rooms with wall-shaking bass impact. Forget lightweight toys—this beautifully finished full-scale system is the most convenient and affordable route to THX multiplex sound.

SKF-980

2-Way Acoustic-Suspension Front Speakers

- 12 cm A-OMF Diaphragm Woofer x 2
- 2.5 cm Soft-Dome Tweeter
- Max. Input Power: 130 W
- Magnetically Shielded

SKC-980

2-Way Acoustic-Suspension Center Speaker

- 12 cm A-OMF Diaphragm Woofer x 2
- 2.5 cm Soft-Dome Tweeter
- Max. Input Power: 130 W
- Magnetically Shielded

SKR-980/SKB-980

2-Way Acoustic-Suspension Surround/ Surround Back Speakers

- 13 cm A-OMF Diaphragm Woofer
- 2.5 cm Soft-Dome Tweeter
- Max. Input Power: 130 W

Note: All speakers feature an impedance of 8 Ω, color-coded speaker terminals and cable, and wall-mounting capability.

SKW-938

Acoustic-Suspension Powered Subwoofer

- 30 cm Cone
- Rated Output Power: 125 W (Minimum Continuous Power, 6 Ω, 100 Hz, 1%, IEC)
- Output Level Control and Auto Standby Function

SPECIFICATIONS

SPEAKER SYSTEM

Speaker Type	
Front	2-Way, Acoustic-Suspension
Center	2-Way, Acoustic-Suspension
Surround	2-Way, Acoustic-Suspension
Surround Back	2-Way, Acoustic-Suspension
Subwoofer	Acoustic-Suspension, Powered
Drivers	
Front	12 cm A-OMF Diaphragm Woofer x 2 2.5 cm Soft-Dome Tweeter
Center	12 cm A-OMF Diaphragm Woofer x 2 2.5 cm Soft-Dome Tweeter
Surround	13 cm A-OMF Diaphragm Woofer 2.5 cm Soft-Dome Tweeter
Surround Back	13 cm A-OMF Diaphragm Woofer 2.5 cm Soft-Dome Tweeter
Subwoofer	30 cm Cone
Frequency Response	
Front	50 Hz–45 kHz
Center	50 Hz–45 kHz
Surround	50 Hz–45 kHz
Surround Back	50 Hz–45 kHz
Subwoofer	20 Hz–100 Hz
Output Sound Pressure Level	
Front	83 dB/W/m
Center	83 dB/W/m
Surround	81 dB/W/m
Surround Back	81 dB/W/m
Max. Input Power	Front/Center/Surround/Surround Back 130 W
Rated Output Power	Subwoofer 125 W (Minimum Continuous Power, 6 Ω, 100 Hz, 1%, IEC)

Nominal Impedance	Front/Center/Surround/Surround Back 8 Ω
Input Sensitivity/Impedance	Subwoofer 280 mV/20 kΩ
General	
Dimensions (W x H x D)	
Front	158 x 433 x 199 mm
Center	433 x 158 x 199 mm
Surround	200 x 275 x 169 mm
Surround Back	200 x 275 x 169 mm
Subwoofer	380 x 444 x 429 mm
Weight	
Front	5.3 kg
Center	5.3 kg
Surround	3.5 kg
Surround Back	3.5 kg
Subwoofer	15.5 kg
CARTON	
Dimensions (W x H x D)	748 x 852 x 513 mm
Weight	51.0 kg

Due to a policy of continuous product improvement, Onkyo reserves the right to change specifications and appearance without notice. A-OMF is a trademark of Onkyo Corporation. THX is a trademark of THX Ltd, which is registered in some jurisdictions. All rights reserved. All other trademarks and registered trademarks are the property of their respective holders.

ONKYO®

Onkyo Corporation Kitahama Chuo Bldg. 2-2-22 Kitahama, Chuo-ku, Osaka 541-0041 JAPAN <http://www.onkyo.com/>
 Onkyo Marketing Asia Limited Unit 1033, 10/F., Star House, No. 3, Salisbury Road, Tsim Sha Tsui, Kowloon, Hong Kong, CHINA Tel: 852-2429-3118 Fax: 852-2428-9039
<http://www.hk.onkyo.com/> (Hong Kong) <http://www.cn.onkyo.com/> (Mainland)

Onkyo U.S.A. Corporation 18 Park Way, Upper Saddle River, N.J. 07458, U.S.A. Tel: 1-201-785-2600 or 800-229-1687 (Toll free) Fax: 1-201-785-2650 <http://www.onkyousa.com/>
 Onkyo Europe Electronics GmbH Liegnitzerstrasse 6, 82194 Grobenzell, GERMANY Tel: 49-8142-4208-10 Fax: 49-8142-4208-202 <http://www.eu.onkyo.com/>