

TA-RW255

DOUBLE CASSETTE DECK

ONKYO
IMAGINATIVE SIGHT & SOUND

CAPTURING THE DETAIL AND CLARITY OF ALL YOUR TAPE RECORDINGS WITHOUT A HINT OF TAPE HISS



DOLBY
B-C TYPE NR

RI

Features

- Double deck for tape dubbing
- Deck A for playback Deck B for recording and playback
- NORMAL and HIGH speed dubbing capability
- Auto-reverse on both decks: Auto-reverse record on Deck B
- CD player-to-deck synchronous recording
- Dolby® B and C noise reduction
- 8-segment FL peak level indicators (with peak hold)
- Automatic tape selector
- Auto-space rec mute
- 4-digit electronic tape counter
- Vibration-proof chassis
- Aluminum front panel
- RI (Remote Interactive) system compatible

SPECIFICATIONS

Formal	Auto reverse/Double deck
Track Format	4 tracks/2 channels
Record System	AC Bias
Erase System	AC Erase
Tape Speed	4.76 cm/sec
Wow and Flutter	0.13 % (WRMS)
Frequency Response	
Metal Position Tape	30 Hz-15 kHz/± 3 dB
High Position Tape	30 Hz-14 kHz/± 3 dB
Normal Position Tape	30 Hz-13 kHz/± 3 dB
Signal-to-Noise Ratio	
Metal Position/Type IV, Dolby NR OFF	56 dB
High Position/Type II, Dolby NR OFF	55 dB
Normal Position/Type I, Dolby NR OFF	50 dB
<i>A noise reduction of 10 dB above 5 kHz and 5 dB at 1 kHz is possible with the Dolby B NR.</i>	
<i>A noise reduction of 20 dB at 5 kHz is possible with the Dolby C NR.</i>	
Input Terminals	
Input Sensitivity	80 mV
Input Impedance	50 kΩ
Output Terminals	
Standard Output Level	500 mV
Output Load Impedance	More than 50 kΩ
Motors	DC Servo Motor 1 + 1
Heads	
PB Head	Special Hard Permalloy x 1
Rec/PB Head	Special Hard Permalloy x 1
Erase Head	Ferrite x 1
Controls	Dolby NR, Reverse Mode, Rec Level, Eject, Tape Counter Deck—A/B Select, Counter Reset, Tape Operation, NORM and HIGH Speed Dubbing, Standby, Auto-Space, Main Power
GENERAL	
Power Supply	AC 230-240 V, 50 Hz
Power Consumption	17 W
Standby Power Consumption	0.6 W
Dimensions (W x H x D)	435 x 121 x 303 mm
Weight	4.9 kg

Due to a policy of continuous product improvement, Onkyo reserves the right to change specifications and appearance without notice. Dolby and the double-D symbol are trademarks of Dolby Laboratories.

ONKYO
IMAGINATIVE SIGHT & SOUND

Onkyo Corporation 2-1 Nishshin-cho, Neyagawa-shi, OSAKA 572-8540, JAPAN Tel: +81-72-831-8136 Fax: +81-72-833-5222 <http://www.onkyo.com/>
Onkyo China Limited Units 2102-2107, Metroplaza Tower I, 223 Hing Fong Road, Kwai Chung, N. T., HONG KONG, SAR of China Tel: +852-2429-3118 Fax: +852-2428-9039 <http://www.ch.onkyo.com/>
Onkyo U.S.A. Corporation 18 Park Way, Upper Saddle River, N.J. 07458, U.S.A. Tel: +1-201-785-2600 Fax: +1-201-785-2650 <http://www.onkyousa.com/>
Onkyo Europe Electronics GmbH Liegnitzerstrasse 6, 82194 Grobenzell, GERMANY Tel: +49-8142-4401-0 Fax: +49-8142-4401-555 <http://www.eu.onkyo.com/>